

# *Powerguard International*

## *Invisible Theft Protection*

### **Application Instructions**

#### **PRELIMINARY CONSIDERATIONS**

**Storage:** Labels are a security system, so they should be stored securely. Keep them in a dry, protected place at temperatures between 50 and 90 degrees F. Be sure the labels remain affixed to their backing and out of direct sunlight until application.

**Extra materials needed:** ISOPROPYL ALCOHOL and PAPER TOWELS. If parts are greasy or dirty, clean then with isopropyl alcohol before applying labels.

**Application environment:** If applying outdoors, keep parts and labels dry during application procedure.

#### **Application procedures**

**Determine where to apply the label:** Identify specific parts and the location where the label will be applied. When applied, label shouldn't be visible.

**Parts normally marked include:** Front fenders, bike fenders, hoods, doors, trunk lid, hatch back, tail gate, rear quarter panel.

**Make sure parts are clean:** Before applying labels, make sure parts are free of dirt, oil, grease and moisture. If needed, clean thoroughly with isopropyl alcohol.

**Check label alignment:** Before applying a label, position it over the location to be sure alignment is suitable. Once you apply the label, you cannot remove it without damaging it. Do not apply a label over an existing label.

**Apply label to component:** Carefully place the left edge of the label on the part first. Then, working left to right, gently press the label to the part. Work from the center of the label to the edges to remove any wrinkles or bubbles.

**Secure label to part:** Once you have removed all wrinkles and bubbles, press the label firmly to the part using your thumb. This step is necessary to secure the label to the part.